

Sandhill "Essential" Security System

*\$249.95

Sandhill
SECURITY

Peace of Mind from People You Trust



System Includes:

- ◆ Wireless Control Panel
- ◆ Integrated Internal Siren
- ◆ Internal Message Center with Built-In Microphone
- ◆ 2 Wireless Door or Window Detector
- ◆ 1 Wireless Keychain Remote Control
- ◆ 1 Yard Sign, 2 Window decals



General Specifications

- Supports 7845i and 7845GSM
- Two-way voice
- Ten digit account number
- Supports RF encrypted devices
- Voice prompt clock setting
- Additional voice descriptors
- Full-function Keypad with LCD Display
- Built-in X-10 Home Automation Capability
- Family Message Center with Voice Recording and Playback
- Single Button Operation
- Paging
- Multiple Default Settings for Easy Programming
- Scheduling
- RF Enrollment Speeds Installation of Wireless Keys and Transmitters
- Voice Siren
- Rechargeable Battery Backup
- Full Voice Response
- Remote Downloading
- 8 User Codes
- 84 Event Log
- Chime By Zone
- Quick Exit
- Real-time Clock
- Output Trigger

Technical Specifications

Electrical:

- Voltage Input: 9VAC from plug-in 15VA transformer
- Rechargeable Backup Battery: Six 1.2-volt/cell nickel-metal hydride rated at 1100 mA
- Alarm Sounder:
 - Piezo: 6-14VDC, 30mA max
 - Bell: 6-14VDC, 120mA max (e.g., WAVE2EX)
- Long Range Radio: Rated 12mA@ 12-volt nominal (negative trigger signal)

Integrated Wireless Receiver:

- LYNX receiver supports:
 - 24 zones and four wireless keys
 - Two way wireless devices with status feedback: 5804BDV and 5827BD
 - Diversity Reception with two antennae
 - Indications by zone and low battery indicator

**Initial system cost can be paid over a 12 month period if qualified for Member Rewards.*

Communications:

- Formats supported:
 - Express: 10 characters/sec, DTMF (TouchTone) Data Tones, 1400/2300Hz ACK, 1400H KISSOFF
 - Contact ID Reporting: 10 characters/sec., DTMF (TouchTone) Data Tones, 1400/2300Hz ACK, 1400Hz KISSOFF
 - Low Speed: 10 pulses/sec, 1900Hz Data Tone, 400Hz ACK/KISSOFF
 - Radionics/SESCO: 20 pulses/sec, 1800Hz Data Tone, 2300Hz ACK/KISSOFF. Can report 0-9, B-F
- Line Seize: Double Pole
- Ringing Equivalence: 0.6B
- FCC Registration No.: 5GBUSA-25623-AL-E
- Maximum Zone 1 Resistance: 300 ohms, excluding 2k ohm EOLR
- Physical Dimensions: 10-3/8" W x 7-1/8" H x 1-3/4" D